

## Optimization of Passenger Elevator Design for Apartment Building

Udin Komarudin<sup>1</sup>, Nia Nuraeni Suryaman<sup>2</sup>, Ida Farida<sup>3</sup>

<sup>1</sup>Department of Mechanical Engineering Widyatama University Bandung, Indonesia

<sup>2</sup>Department of Mechanical Engineering Widyatama University Bandung, Indonesia

<sup>3</sup>Department of Mechanical Engineering Widyatama University Bandung, Indonesia

<sup>1</sup>komarudin.mt@widyatama.ac.id, <sup>2</sup>nia.suryaman@widyatama.ac.id, <sup>3</sup>ida.farida@widyatama.ac.id

**Article History:** Received: 10 January 2021; Revised: 12 February 2021; Accepted: 27 March 2021; Published online: 20 April 2021

**Abstract:** An elevator is one of the circulation systems in a building that is classified as a vertical circulation system in the building. Transportation planning in buildings must be in accordance with laws, ministerial regulations, regional regulations and standards, which become a reference in planning procedures. The xxx apartment building located in East Jakarta is an apartment building consisting of 2 towers (Tower A and B), each of which consists of a total of 25 floors (24 floors + 1 basement), 1 floor roof, each 87.3 meters high. , the number of occupants of building A is 727 people and building B is 748 people. Traffic analysis is needed to determine the type of lift suitable for the building. The method used in this research is to use the Indonesian National Standard, SNI 03-6573-2001. From the results of traffic analysis calculations for buildings A and B obtained, the selected elevator for apartment building A is an elevator with a capacity of 15 people (1000 kg) with a speed of 90 mpm, a total of 3 units. And apartment building B is an elevator with a capacity of 15 people (1000 kg) with a speed of 90 mpm, a total of 3 units.

**Keywords:** elevator, apartment, TDG, SNI

### 1. Introduction

An elevator is one of the circulation systems in a building that is classified as a vertical circulation system in the building. In accordance with government regulations, that planning for interior transportation (TDG) must refer to the Indonesian National Standard, SNI 03-6573-2001, 2001 regarding the Design Procedure for a vertical transportation system in buildings (elevators). The xxx apartment building located in East Jakarta is an apartment building consisting of 2 towers (Tower A and B), each of which consists of a total of 25 floors (24 floors + 1 basement), and 1 roof floor.

Basement floors are used for parking areas and are also used as M / E Utility Rooms (Transformer Rooms, Panel Rooms, Genset Rooms, Pump Rooms, etc.). Floors 1 to 5 are used as the Lobby, Parking and Public Facilities, while floors 6 to 24 are used as residences. The roof floor is used as a placement for mechanical supporting equipment such as a top water tank, distribution pump, exhaust fan, gondola and so on. It is necessary to design the type of lift in accordance with the provisions, SNI 03-6573-2001, so that the elevator service is more optimal in normal conditions or in emergencies..

Rules used as a reference in elevator planning

- PERDA (Regional Regulation) of the Special Capital Region of Jakarta Number 7 of 2010 concerning Buildings within the Special Capital Region of Jakarta or the latest edition.
- PERDA (Regional Regulation) of the Special Capital Region of Jakarta Number 8 of 2008 concerning Fire Hazard Management in the Special Capital Region of Jakarta or its latest edition.
- DKI Regional Regulation No. 3 of 1975 concerning Fire Lift Operations and Fire Rating.
- Guidelines for the Installation of Elevators Electricity No.3 1987
- Safety Code for the Elevator
- Indonesian National Standard (SNI) 05-2189-1999 regarding the definition of elevator and escalator terms
- Indonesian National Standard (SNI) 03-2190-1999 concerning General Conditions for Passenger Elevator Construction which is run by Traction Motor.
- Indonesian National Standard (SNI) 03-6573-2001 concerning Design Procedures for Vertical Transportation Systems in Buildings (Elevators).

### 2. Elevator

An elevator is a vertical transportation tool in a vertical building, which is used to carry people or goods. Lifts are usually used in high-rise buildings above 3 floors. One of those who introduced the lift was Elisa Graves Otis in 1853, where in 1857 the first passenger lift was installed in a building in New York. So that in 1873 more than

200 elevators were used in various office buildings and hotels in America. The elevator has developed, where in 1903 the gearless traction elevator was introduced.

The lift mechanism (geared or gearless) is a lift carriage depending on the sliding space by steel hoist ropes, pulley pulleys, and counterweights. The carriage weight and counterweight provide traction between the pulley and hoist ropes, so that it moves and holds the carriage without slipping, and the carriage and counterweight move along the rails

1) Normal Condition Elevator System

The lift works in a joint work (Operation group). Elevators are controlled by supervisory. Elevator responsive to Floor Calls (PL) and Train Calls (PK). The driving machine is a type of traction (geared machine) with an AC induction motor with VVVF (Varying Voltage Varying Frequency) control.

2) Emergency Condition Elevator

a) Fire

If a fire alarm is detected, a signal from the fire alarm system will inform passengers that the elevator will descend into the lobby for use by the fire team. If at that time the elevator is moving upwards will stop at the next closest floor, without opening the door and immediately going down non-stop to the lobby floor or a floor planned. If at that time the elevator is moving down, the elevator continues its journey directly to the lobby. The elevator, which is parked on a floor, immediately closes the door and leaves for the Lobby floor. The door that closes is regulated not to reopen, even if the safety shoe (edge) is offended by someone or the DC button is pressed. All the above operations without heeding floor calls and train calls. When all the elevators reach the lobby, the doors open. One of the lifts is ready for use by the pemdam team by using the ignition key. If the fire switch returns to normal, the FIREMAN's SERVICE signal goes out and the elevator works normally. The fire fighting elevator is powered by an emergency generator. The power line must be fire resistant for 1 hour and installed in fire protection.

b) Earthquake.

the elevator is equipped with seismic sensors, the lift will land on the nearest floor under load in the event of an earthquake. Another goal is to prevent the rails from being damaged by shocks (pendulum effect).

c) Jamming

Jamming in the elevator by a PLN power source that has been cut off, must be resolved with an Automatic Rescue Device (ARD). After the PLN power is off, the emergency light will turn on. A few seconds later the elevator will go to the nearest floor under weights and the elevator door will open. Elevator congestion due to the safety function works, for example overspeed and due to technical errors (maintenance and worn components) can be overcome by remote elevator monitoring (REM), which is by installing a modem via the telephone line automatically recorded jams on the maintenance contractor's computer or as soon as possible repaired.

d) Emergency Electric Power

The emergency power generator must be able to replace the loss of the PLN power source in a short time automatically, because the emergency power source is not fully powered, then automatically one by one the elevator descends to the lobby. Upon arriving at the lobby the doors opened to let everyone out. Then there are several selected lifts that automatically get energy rations to operate again.

### 3. Metodology

The methodology used in this research is to refer to the Indonesian National Standard, SNI 03-6573-2001, starting from:

- 1) Building Data
- 2) Traffic Zoning
- 3) Rush-Peak Hour
- 4) Average waiting time

### 4. Design and calculation

The design of the transportation system in the xxx apartment building in East Jakarta refers to the regulations, laws of the Republic of Indonesia, Indonesian National standards and existing literature.

1) Building Data :

The building consists of 2 buildings, Apartment A and Apartment B.

a) Apartement A

|                  |   |                           |
|------------------|---|---------------------------|
| Type of building | : | Apartement A              |
| Total Floor      | : | 25 (24 floors + Basement) |

- Building height : 87,3 meter
- Occupants : 727 person
- Floor area : 63,871 m2 (average)
- b) Apartemen B
  - Type of building : Apartemen B
  - Total Floor : 25 (24 floors + Basement)
  - Building height : 87,3 meter
  - Occupants : 748 person
  - Floor area : 63,871 m2 (average)

2) Traffic Analysis

Traffic analysis for lift building A and building B is based on the Indonesian National Standard, referring to the reference SNI 03-6573-2001 Table 5.2.2, is the Average Waiting Time (AWT) at Main Lobby and Circulation Flow Demand.

| No | Building          | AWT (second) | Circulation Flow Demand (%) | Circulation Busy time |
|----|-------------------|--------------|-----------------------------|-----------------------|
| 1  | Luxurious Office  | 25 - 35      | 10 - 12                     | Morning, Up           |
| 2  | Commercial Office | 25 - 35      | 11 - 13                     | Morning, Up           |
| 3  | Agency Office     | 30 - 40      | 14 - 17                     | Morning, Up           |
| 4  | Star Hotel        | 40 - 60      | 8 - 10                      | Midday, balanced      |
| 5  | Hotel Resort      | 60 - 90      | 6 - 8                       | Morning, Down         |
| 6  | Hospital          | 40 - 60      | 10                          | Midday, balanced      |
| 7  | Apartement        | 60 - 90      | 6 - 8                       | Morning, Down         |
| 8  | Lecture Building  | 40 - 90      | 12.5 - 25                   | Morning, Up<br>Midday |

According to apartment SNI standards are:

- Average Waiting Time: 60–90 seconds
- Circulating Current Demand: 6 - 8%

Traffic analysis calculations with 4 alternative simulations (alt-1, alt-2, alt-3, alt-4) for several variables of elevator capacity and speed.

a) Traffic Analysis, building A

| Simulation | Speed      | Capacity  |
|------------|------------|-----------|
| Alt-1      | 90<br>mpm  | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |
| Alt-4      |            | 17 person |
| Alt-1      | 105<br>mpm | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |
| Alt-4      |            | 17 person |
| Alt-1      | 120<br>mpm | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |
| Alt-4      |            | 17 person |

**TRAFFIC ANALYSIS**  
Alternatif 1 (90 mpm, 9 person)

**TOWER - A**

|   |                                  |   |
|---|----------------------------------|---|
| <p>PROJECT: JAKARTA CEMON PARK</p> <p>MODEL: APARTMENT</p> <p>BLOK: APARTMENT</p> | <p><b>III ALL FLOOR FREE</b></p> | <p><b>MAIN SPECIFICATION</b></p> <p>No. of elevators : 3</p> <p>Rated speed (rpm) : 90</p> <p>Rated Load (person) : 9</p> <p>No. of stops : 25</p> <p>SL (Travel) (m) : 83.4</p> <p>Running speed : No</p> <p>Entrance type : Center OP</p> <p>Opening (W : unit) : 900</p> <p>Population (person) : 727</p> <p>Floor area (m<sup>2</sup>) : 63871.42</p> |
|---|----------------------------------|---|

(Rev : 14-Mar-21 22:55)

| symbol ( unit )    | formula | result |
|--------------------|---------|--------|
| No. of elevator(s) | n       | 3      |

Data for calculation: .....

**TRAFFIC ANALYSIS**  
Alternatif 3 (90 mpm, 15 person)  
**TOWER - A**

PROJECT: JAKARITA CROWN PARK  
MODEL: APARTMENT  
BLDG: APARTMENT

**III ALL FLOOR FREE**

**MAIN SPECIFICATION**

No. of elevators : 3  
Rated speed (rpm) : 90  
Rated load (persons) : 15  
No. of stops : 25  
SL (Travel) (m) : 83.4  
Running speed : No  
Entrance type : Center OP  
Opening (W) (mm) : 900  
Population (persons) : 727  
Floor area (m<sup>2</sup>) : NA

|   | symbol (unit)        | formula                     | result        |  |
|---|----------------------|-----------------------------|---------------|--|
| No. of elevator(s)                                | n                    |                             | 3             | Data for calculation                       |
| Elevator speed                                    | V (m/sec)            | Rated speed / 60            | 1.5           |  |
| No. of passengers                                 | ru (person)          |                             | 6             |  |
|   | rd (person)          |                             | 4.5           |  |
| No. of expected stops in local service section    | fla                  | $N \cdot (1 - ((N-1)/N)^n)$ | 5.384         | N: 23                                      |
|   | fld                  | $N \cdot (1 - ((N-1)/N)^n)$ | 4.169         |  |
| No. of stops in express service section           | fe                   | 0                           | 0             |  |
| No. of expected stops in the entire section       | F                    | fla + fld                   | 9.553         |  |
| Average running distance in local service section | Su (m)               | SL / fla                    | 15.49         |  |
|   | Sd (m)               | SL / fld                    | 20.004        |  |
| Minimum running distance                          | 2Su (m)              |                             | 3             | See: 1.5                                   |
| Time in<br><br>Local                              | Su < 2Sa             | tru x fla                   | 0             | tru: 8.602                                 |
|   | Sd < 2Sa             | trd x fld                   | 0             | trd: 9.672                                 |
|   | Su >= 2Sa            | SL / V + ta x fla           | 66.368        | ta: 2                                      |
|   | Sd >= 2Sa            | SL / V + ta x fld           | 63.938        |  |
|   | express              | 0                           | 0             | td: 3.25                                   |
| Door-opening & closing time                       | Td (sec)             | td x F                      | 21.971        | td: 2.3                                    |
| Passenger entrance & exit time                    | Tp (sec)             | ru x tpu + rd x tpd         | 35.625        | tp: 3.5                                    |
| Time loss   | Tl (sec)             | tl x Td + Tl                | 5.759         | tl: 0.1                                    |
| One round trip time                               | RTF (sec)            | Tr + Tp + Td + Tl           | 193.661       |  |
| Average waiting interval                          | Tav (sec)            | RTF / n                     | <b>64.55</b>  |  |
| 5-minute capacity of each elevator's              | P' (person)          | 5 x 60 x (ru+rd) / RTF      | 16.265        |  |
| 5-minute capacity of all elevators'               | P (person)           | P' x n                      | <b>48.795</b> |  |
| Floor area  | Fa (M <sup>2</sup> ) |                             | NA            | no. of floors in local section             |
| Rental ratio                                      | Rz                   |                             | NA            | no. of floors in local section             |
| Effective floor area of each floor                | EF (M <sup>2</sup> ) |                             | NA            | no. of floors in local section             |
| Area occupied by one person                       | Ao (M <sup>2</sup> ) |                             | NA            | door opening & closing time per one stop   |
| Floor population                                  | Fp (person)          |                             | NA            | average entrance & exit time per passenger |
| Total building population                         | Q (person)           |                             | 727           | stop standing time                         |
| 5-minute handling capacity                        | CC (%)               | P / Q x 100                 | <b>6.71</b>   | door opening time                          |

b) Traffic Analysis, building B

| Simulation | Speed      | Capacity  |
|------------|------------|-----------|
| Alt-1      | 90<br>mpm  | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |
| Alt-4      |            | 17 person |
| Alt-1      | 105<br>mpm | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |
| Alt-4      |            | 17 person |
| Alt-1      | 120<br>mpm | 9 person  |
| Alt-2      |            | 11 person |
| Alt-3      |            | 15 person |

|       |           |
|-------|-----------|
| Alt-4 | 17 person |
|-------|-----------|

| TRAFFIC ANALYSIS                                  |                      |   |                       |
|---|----------------------|---|-----------------------|
| Alternatif 1 (90 steps, 9 person)                 |                      |   |                       |
| TOWER - B   |                      |   |                       |
| PROJECT : JAKARTA CLIN PARK                       |                      | MAIN SPECIFICATION                      |                       |
| MODEL : APARTMENT                                 |                      | No. of elevators : 3                    |                       |
| BLDG : APARTMENT                                  |                      | Rated speed (m/s) : 90                  |                       |
|   |                      | Rated Load (person) : 9                 |                       |
|   |                      | No. of stops : 25                       |                       |
|   |                      | SL (Travel, m) : 83.4                   |                       |
|   |                      | Running open : No                       |                       |
|   |                      | Entrance type : Center OP               |                       |
|   |                      | Opening (W, mm) : 900                   |                       |
|   |                      | Population (person) : 748               |                       |
|   |                      | Floor area (m <sup>2</sup> ) : 63871.42 |                       |
| (Rev : 14-Mar-21 22:55)                           |                      |   |                       |
| symbol ( unit )                                   | formula              | result                                  |                       |
| No. of elevator(s)                                | n                    | 3                                       | Data for calculation: |
| Elevator speed                                    | V (m/sec)            | Rated speed / 60                        | 1.5                   |
| No. of passengers                                 | ru (person)          |   | 3.6                   |
|   | rd (person)          |   | 2.7                   |
| No. of expected stops in local service section    | fla                  | $N(1 - ((N - 1) / N)^{ru})$             | 3.401                 |
|   | fld                  | $N(1 - ((N - 1) / N)^{rd})$             | 2.601                 |
| No. of stops in express service section           | fe                   | 0                                       |                       |
| No. of expected stops in the entire section       | F                    | fla + fld                               | 6.002                 |
| Average running distance in local service section | Su (m)               | SL / fla                                | 24.522                |
|   | Sd (m)               | SL / fld                                | 32.064                |
| Minimum running distance                          | 2Sa (m)              |   | 3                     |
|   | Su < 2Sa             | tru x fla                               | 0                     |
|   | Sd < 2Sa             | trd x fld                               | 0                     |
|   | Su >= 2Sa            | SL / V + ta x fla                       | 62.402                |
|   | Sd >= 2Sa            | SL / V + ta x fld                       | 60.802                |
| Door-opening & closing time                       | Td (sec)             | td x F                                  | 13.804                |
| Passenger entrance & exit time                    | Tp (sec)             | ru x tpu + rd x tpd                     | 21.375                |
| Time loss   | Tl (sec)             | tl x (Td + Tp)                          | 3.517                 |
| One round trip time                               | RTT (sec)            | Tr + Tp + Td + Tl                       | 161.9                 |
| Average waiting interval                          | Tav (sec)            | RTT / n                                 | 53.96                 |
| 5-minute capacity of each elevator's              | P' (person)          | 5 x 60 x (ru+rd) / RTT                  | 11.673                |
| 5-minute capacity of all elevators'               | P (person)           | P' x n                                  | 35.019                |
| Floor area  | Fa (M <sup>2</sup> ) |   | NA                    |
| Rental ratio                                      | Rr                   |   | NA                    |
| Effective floor area of each floor                | Ef (M <sup>2</sup> ) |   | NA                    |
| Area occupied by one person                       | Ao (M <sup>2</sup> ) |   | NA                    |
| Floor population                                  | Fp (person)          |   | NA                    |
| Total building population                         | Q (person)           |   | 748                   |
| 5-minute handling capacity                        | CC (%)               | P' / Q x 100                            | 4.68                  |

| TRAFFIC ANALYSIS                                  |                      |                                   |                       |
|---|----------------------|-----------------------------------|-----------------------|
| Alternatif 3 (90 steps, 15 person)                |                      |                                   |                       |
| TOWER - B   |                      |                                   |                       |
| PROJECT : JAKARTA CLIN PARK                       |                      | MAIN SPECIFICATION                |                       |
| MODEL : APARTMENT                                 |                      | No. of elevators : 3              |                       |
| BLDG : APARTMENT                                  |                      | Rated speed (m/s) : 90            |                       |
|   |                      | Rated Load (person) : 15          |                       |
|   |                      | No. of stops : 25                 |                       |
|   |                      | SL (Travel, m) : 83.4             |                       |
|   |                      | Running open : No                 |                       |
|   |                      | Entrance type : Center OP         |                       |
|   |                      | Opening (W, mm) : 900             |                       |
|   |                      | Population (person) : 748         |                       |
|   |                      | Floor area (m <sup>2</sup> ) : NA |                       |
| (Rev : 15-Mar-21 9:12)                            |                      |                                   |                       |
| symbol ( unit )                                   | formula              | result                            |                       |
| No. of elevator(s)                                | n                    | 3                                 | Data for calculation: |
| Elevator speed                                    | V (m/sec)            | Rated speed / 60                  | 1.5                   |
| No. of passengers                                 | ru (person)          |                                   | 6                     |
|   | rd (person)          |                                   | 4.5                   |
| No. of expected stops in local service section    | fla                  | $N(1 - ((N - 1) / N)^{ru})$       | 5.384                 |
|   | fld                  | $N(1 - ((N - 1) / N)^{rd})$       | 4.169                 |
| No. of stops in express service section           | fe                   | 0                                 |                       |
| No. of expected stops in the entire section       | F                    | fla + fld                         | 9.553                 |
| Average running distance in local service section | Su (m)               | SL / fla                          | 15.49                 |
|   | Sd (m)               | SL / fld                          | 20.004                |
| Minimum running distance                          | 2Sa (m)              |                                   | 3                     |
|   | Su < 2Sa             | tru x fla                         | 0                     |
|   | Sd < 2Sa             | trd x fld                         | 0                     |
|   | Su >= 2Sa            | SL / V + ta x fla                 | 66.368                |
|   | Sd >= 2Sa            | SL / V + ta x fld                 | 63.938                |
| Door-opening & closing time                       | Td (sec)             | td x F                            | 21.971                |
| Passenger entrance & exit time                    | Tp (sec)             | ru x tpu + rd x tpd               | 35.625                |
| Time loss   | Tl (sec)             | tl x (Td + Tp)                    | 5.759                 |
| One round trip time                               | RTT (sec)            | Tr + Tp + Td + Tl                 | 193.661               |
| Average waiting interval                          | Tav (sec)            | RTT / n                           | 64.55                 |
| 5-minute capacity of each elevator's              | P' (person)          | 5 x 60 x (ru+rd) / RTT            | 16.265                |
| 5-minute capacity of all elevators'               | P (person)           | P' x n                            | 48.795                |
| Floor area  | Fa (M <sup>2</sup> ) |                                   | NA                    |
| Rental ratio                                      | Rr                   |                                   | NA                    |
| Effective floor area of each floor                | Ef (M <sup>2</sup> ) |                                   | NA                    |
| Area occupied by one person                       | Ao (M <sup>2</sup> ) |                                   | NA                    |
| Floor population                                  | Fp (person)          |                                   | NA                    |
| Total building population                         | Q (person)           |                                   | 748                   |

|                                      |                      |                        |                   |   |
|--------------------------------------|----------------------|------------------------|-------------------|---|
| Minimum running distance             | 2Sa (m)              |                        | 3                 | Sc: 1.5   |
|                                      | Su < 2Sa             | tru x fla              | 0                 | tru: 8.602                                      |
|                                      | Sd < 2Sa             | trd x fld              | 0                 | trd: 9.672                                      |
|                                      | Su >= 2Sa            | Tr (sec)               | SL / V + ta x fla | ta: 2   |
|                                      | Sd >= 2Sa            |                        | SL / V + ta x fld |   |
|                                      | express              |                        | 0                 | pd: 3.25  |
| Door-opening & closing time          | Td (sec)             | td x F                 | 21.971            | td: 2.3   |
| Passenger entrance & exit time       | Tp (sec)             | ru x tpu + rd x tpd    | 35.625            | tpu: 3.5  |
| Time loss                            | Tl (sec)             | tl x (Td + Tp)         | 5.759             | tl: 0.1   |
| One round trip time                  | RTT (sec)            | Tr + Tp + Td + Tl      | 193.661           |   |
| Average waiting interval             | Tav (sec)            | RTT / n                | 64.55             |   |
| 5-minute capacity of each elevator's | P' (person)          | 5 x 60 x (ru+rd) / RTT | 16.265            | Legend:   |
| 5-minute capacity of all elevators'  | P (person)           | P' x n                 | 48.795            | Sc: no. of floors in local section              |
| Floor area                           | Fa (M <sup>2</sup> ) |                        | NA                | Sc: accelerated (decelerated) dist.             |
| Rental ratio                         | Rr                   |                        | NA                | tl: time loss                                   |
| Effective floor area of each floor   | Ef (M <sup>2</sup> ) |                        | NA                | ta: accelerated (decelerated) time              |
| Area occupied by one person          | Ao (M <sup>2</sup> ) |                        | NA                | td: door-opening & closing time per one stop    |
| Floor population                     | Fp (person)          |                        | NA                | tpu: average entrance & exit time per passenger |
| Total building population            | Q (person)           |                        | 748               | tru: up running time                            |

5. Result and evaluation

1) Traffic Analysis Results

Apartment Building A

| Resume Traffic Analysis (Passenger elevator) |                |                   |             |               |                              |                   |      |
|--|----------------|-------------------|-------------|---------------|------------------------------|-------------------|------|
| Alternatif                                   | Total elevator | Capacity (person) | Speed (mpm) | Floor service | SNI 03-673-2001 (Apartement) |                   | Note |
|  |                |                   |             |               | Circulation Flow (6% - 8%)   | AWT (60 - 90 sec) |      |
| ALT -1                                       | 3              | 9                 | 90          | 25            | 4.81                         | 53.96             |      |
| ALT -2                                       | 3              | 11                | 90          | 25            | 5.52                         | 57.55             |      |
| ALT -3                                       | 3              | 15                | 90          | 25            | 6.71                         | 64.55             | ok   |
| ALT -4                                       | 3              | 17                | 90          | 25            | 7.22                         | 67.97             | ok   |
| ALT -1                                       | 3              | 9                 | 105         | 25            | 5.25                         | 49.47             |      |
| ALT -2                                       | 3              | 11                | 105         | 25            | 5.97                         | 53.21             |      |
| ALT -3                                       | 3              | 15                | 105         | 25            | 7.15                         | 60.53             | ok   |
| ALT -4                                       | 3              | 17                | 105         | 25            | 7.66                         | 64.09             | ok   |
| ALT -1                                       | 3              | 9                 | 120         | 25            | 5.63                         | 46.10             |      |
| ALT -2                                       | 3              | 11                | 120         | 25            | 6.35                         | 49.97             |      |
| ALT -3                                       | 3              | 15                | 120         | 25            | 7.53                         | 57.51             |      |
| ALT -4                                       | 3              | 17                | 120         | 25            | 8.02                         | 61.19             |      |

Gedung Apartemen B

| Resume Traffic Analysis (Passenger elevator) |                |                   |             |               |                              |                   |      |
|--|----------------|-------------------|-------------|---------------|------------------------------|-------------------|------|
| Alternatif                                   | Total elevator | Capacity (person) | Speed (mpm) | Floor service | SNI 03-673-2001 (Apartement) |                   | Note |
|  |                |                   |             |               | Circulation Flow (6% - 8%)   | AWT (60 - 90 sec) |      |
| ALT -1                                       | 3              | 9                 | 90          | 25            | 4.68                         | 53.96             |      |
| ALT -2                                       | 3              | 11                | 90          | 25            | 5.36                         | 57.55             |      |
| ALT -3                                       | 3              | 15                | 90          | 25            | 6.52                         | 64.55             | ok   |
| ALT -4                                       | 3              | 17                | 90          | 25            | 7.02                         | 67.97             | ok   |
| ALT -1                                       | 3              | 9                 | 105         | 25            | 5.10                         | 49.47             |      |
| ALT -2                                       | 3              | 11                | 105         | 25            | 5.80                         | 53.21             |      |
| ALT -3                                       | 3              | 15                | 105         | 25            | 6.95                         | 60.53             | ok   |
| ALT -4                                       | 3              | 17                | 105         | 25            | 7.44                         | 64.09             | ok   |
| ALT -1                                       | 3              | 9                 | 120         | 25            | 5.48                         | 46.10             |      |
| ALT -2                                       | 3              | 11                | 120         | 25            | 6.18                         | 49.97             |      |
| ALT -3                                       | 3              | 15                | 120         | 25            | 7.32                         | 57.51             |      |
| ALT -4                                       | 3              | 17                | 120         | 25            | 7.79                         | 61.19             | ok   |

2) Analisis

The results of the traffic analysis for building A, obtained 4 alternative lift options that match the criteria, as follows:

| Alternatif | Total elevator | Capacity (person) | Speed (mpm) | Floor service | SNI 03-673-2001 (Apartement) |                   | Note |
|------------|----------------|-------------------|-------------|---------------|------------------------------|-------------------|------|
|            |                |                   |             |               | Circulation Flow (6% - 8%)   | AWT (60 - 90 sec) |      |
| ALT -3     | 3              | 15                | 90          | 25            | 6.71                         | 64.55             | ok   |
| ALT -4     | 3              | 17                | 90          | 25            | 7.22                         | 67.97             | ok   |
| ALT -3     | 3              | 15                | 105         | 25            | 7.15                         | 60.53             | ok   |
| ALT -4     | 3              | 17                | 105         | 25            | 7.66                         | 64.09             | ok   |

The results of the traffic analysis for building B, obtained 5 alternative lift options that match the criteria, as follows:

| Alternatif | Total elevator | Capacity (person) | Speed (mpm) | Floor service | SNI 03-673-2001 (Apartement) |                   | Note |
|------------|----------------|-------------------|-------------|---------------|------------------------------|-------------------|------|
|            |                |                   |             |               | Circulation Flow (6% - 8%)   | AWT (60 - 90 sec) |      |
| ALT -3     | 3              | 15                | 90          | 25            | 6.52                         | 64.55             | ok   |
| ALT -4     | 3              | 17                | 90          | 25            | 7.02                         | 67.97             | ok   |
| ALT -3     | 3              | 15                | 105         | 25            | 6.95                         | 60.53             | ok   |
| ALT -4     | 3              | 17                | 105         | 25            | 7.44                         | 64.09             | ok   |
| ALT -4     | 3              | 17                | 120         | 25            | 7.79                         | 61.19             | ok   |

Selected elevator for building A and B :

Elevator capacity 15 person and speed 90 mpm. This elevator was chosen because the price is the cheapest compared to others

### 3) Analisis Result

#### Building A

| Description            | Passenger Lift     | Service/Fire Lift  |
|------------------------|--------------------|--------------------|
| Code                   | PL.1, PL.2, PL.3   | SV.1               |
| Quantity               | 3 unit             | 1 unit             |
| Fungsi                 | Passenger          | Service / Fire     |
| Capacity               | 15 orang (1000 kg) | 22 orang (1500 kg) |
| Speed                  | 90 mpm             | 90 mpm             |
| Floor Serve            | Basement ~ Lt.24   | Basement ~ Atap    |
| Travel                 | 83,4 m             | 87,3 m             |
| Car size internal      | 1600 x 1500 mm     | 2000 x 1650 mm     |
| Hoistway Dimension     | 2100 x 2300 mm     | 2800 x 2450 mm     |
| Door Width/Type        | 900 x 2100 mm / CO | 1100 x 2100 / CO   |
| Over Head              | 4850 mm            | 4850 mm            |
| Pit Depth              | 1850 mm            | 1850 mm            |
| Machine Room Location  | Roof               | Roof               |
| Machine Room Dimension | min. 2200 mm       | min. 2200 mm       |
| Control System         | Duplex             | Simplex            |
| Power                  | 18 KW              | 18 KW              |

#### Building B

| Description            | Passenger Lift     | Service/Fire Lift  |
|------------------------|--------------------|--------------------|
| Code                   | PL.1, PL.2, PL.3   | SV.1               |
| Quantity               | 3 unit             | 1 unit             |
| Fungsi                 | Passenger          | Service / Fire     |
| Capacity               | 15 orang (1000 kg) | 22 orang (1500 kg) |
| Speed                  | 90 mpm             | 90 mpm             |
| Floor Serve            | Basement ~ Lt.24   | Basement ~ Atap    |
| Travel                 | 83,4 m             | 87,3 m             |
| Car size internal      | 1600 x 1500 mm     | 2000 x 1650 mm     |
| Hoistway Dimension     | 2100 x 2300 mm     | 2800 x 2450 mm     |
| Door Width/Type        | 900 x 2100 mm / CO | 1100 x 2100 / CO   |
| Over Head              | 4850 mm            | 4850 mm            |
| Pit Depth              | 1850 mm            | 1850 mm            |
| Machine Room Location  | Roof               | Roof               |
| Machine Room Dimension | min. 2200 mm       | min. 2200 mm       |
| Control System         | Duplex             | Simplex            |
| Power                  | 18 KW              | 18 KW              |

#### 4) Elevator control

All passenger lifts and service lifts are of type AC-Variable Voltage / Variable Frequency (AC-VVVF) with micro-processor (Computerized) control, both for Single Lift (Selective Collective) and as a group (Supervisory-Group Control)

#### 5) Elevator Operational System

- Passenger Elevator operation using duplex supervisory group control
- The task of each elevator is controlled by a supervisory group control panel using a micro-processor.
- One of the elevators will stop on a specific floor call by a train call, if the direction of the elevator matches the call.
- A button press can be received by the elevator control management for 5 seconds before the lift stops at the floor specified.

- A person entering an elevator is given the opportunity to press a button (priority as long as the destination is the same as the direction of the lift) before the elevator door closes. If that time interval, the button is not pressed then the train is free to go to the direction where there is a call.
- All calls to the floor upward will be served by an upward elevator, on the other hand, a downward floor call is served by an elevator that moves downward.
- The lift will reverse direction if the last call / request has been served and will then serve floor calls and train requests in the opposite direction.
- If the elevator is on duty, one of the lifts will be waiting at the Lobby, the other elevator will stop where it was last served. If this elevator serves the lobby floor the last time, the standby elevator in the lobby will move to "Home Landing" where the home landing is placed 2/3 of the building floor.
- The elevator waiting in the lobby will leave, if the other elevator is busy serving floor calls.
- Passenger elevator serves Ground to 24 floors
- Lift service serves all floors. This lift also functions as a fire lift in an emergency

6) There was a fire in the elevator operating system

When a fire occurs or the General Alarm is active, through the Master Control Fire Alarm (MCFA) all elevators are ordered to descend to the 1st floor and all calls from other floors will not be served. In this condition, only the Service Lift can be operated manually via the Fireman Switch on the 1st floor near the elevator. The lift service is operated by the Fire Brigade Team for the purposes of both extinguishing operations and evacuating residents when a fire occurs.

- The power source comes from an emergency generator
- The cable must be fire resistance cable for 1 (one) hour and installed in fire protection.
- Minimum train area of 2.0 m<sup>2</sup>
- The tempo of running the fire lift to the top should not take more than 60 seconds.
- If the Switch (Toggle Switch) in the glass case has been activated, the "Fireman Service" signal will light up to inform passengers that the elevator will descend into the lobby for use by the fire team and will not serve all calls and requests.
- If at that time the elevator moving upwards will stop at the next closest floor, without opening the door and immediately departing non-stop to the lobby level (or other floor planned)
- If at that time the elevator is moving down, the elevator continues the trip directly to the lobby.
- The elevator is parked on a floor, it will immediately close the door and go to the lobby floor.
- The door that closes is set not to reopen, even if the safety edge is offended by someone or the door open button is pressed and all orders / calls will not be served.
- When all passenger lifts have reached the lobby, the elevator doors will open.
- Service Lift which also functions as a fire lift is ready to be used by firefighters by using the ignition key.
- If the fire switch returns to normal, then the "FIREMANS SERVICE" signal will go out and all of its passenger lifts will immediately work normally.

The need for power for the fire lift is supplied by PLN and the generator using FRC cables so that there is no loss of electrical power during the evacuation.

In addition, the lift cannot be considered as part of the procedure for rescue or evacuation from fire hazards, but can still be used as an escape when the initial fire siren sounds.

**6. conclusion**

The analysis traffic for apartment building xxx located in East Jakarta is obtained for apartment building A is a type of passenger elevator with a capacity of 15 person (1000 kg) with a speed of 90 mpm, total 3 units. And apartment building B is an elevator with a capacity of 15 people (1000 kg) with a speed of 90 mpm, a total of 3 units.

**References**

1. Standar Nasional Indonesia SNI 03-6573-2001: Tata cara perancangan system transportasi vertical dalam gedung (LIF).
2. Standar Nasional Indonesia SNI 05-2189-1999: Istilah untuk lift dan escalator.
3. Standar Nasional Indonesia SNI 03-2190: Konstruksi lift penumpang dengan motor traksi.
4. Prakash, G., Darbandi, M., Gafar, N., Jabarullah, N. H., & Jalali, M. R. (2019). A New Design of 2-Bit Universal Shift Register Using Rotated Majority Gate Based on Quantum-Dot Cellular Automata Technology. *International Journal of Theoretical Physics*, 58(9), 3006-3024.
5. Dibner, D. R. (2015). Building Additions



6. Design. New York: Mc Graw-Hill
7. Book Company