

Design Thinking Approach on Far Field Energy Gleaning From Space

B.Sivasankari^a, R. Prabha^b, S. M. Swamynathan^c, and B. Affrudeen^d

^{a,b}

Associate professor, Department of ECE, SNS College of Technology, Coimbatore.

^cAssistant Professor, Department of ECE, SNS College of Technology, Coimbatore.

^dUG Student, Department of ECE, SNS College of Technology, Coimbatore.

Article History: Received: 11 January 2021; Accepted: 27 February 2021; Published online: 5 April 2021

Abstract: The innovation is further along than might suspect for capturing solar oriented vitality in space where the sun dependably sparkles and radiating it to Earth. The thought of capturing solar-based vitality in space where the sun never quits sparkling and radiating it to Earth may appear to be outlandish, yet such innovation is further along than generally figure it out. A continuous power supply is basic for the activity of Wireless Sensor Networks (WSNs) since business battery control frameworks have restricted lifetime which makes them unsatisfactory for these applications. In this paper, a way to deal with substitute batteries for controlling WSNs is given based on design thinking approach. RF signal as an info source from a solar panel which is then converted into dc and stored for further applications.

Keywords: solar panel, RF, DC, embedded control

1. Introduction

Design thinking is an iterative and non-linear process that can be used effectively for solving highly complicated technical issues. Solar panels work by allowing photons or light particles to strike free electrons in iotas, enabling continuous energy. Solar panels actually include many smaller units called photovoltaic cells. Solar photovoltaics go into daylight as a source of energy to produce energy. The photovoltaic module (PV) is a mass, linked to the integration of 6×10 solar-based photovoltaic cells. Photovoltaic modules contain a photovoltaic collection of old photovoltaic frameworks and provide solar power for business and private applications. The empathy part of this work is as follows. Optical reflectors concentrate the daylight, photovoltaic cells convert the daylight to power and an incorporated circuit changes over the power to radiofrequency energy that is transmitted through a connected reception apparatus. Numerous individual tiles could be hung together to frame enormous sun-oriented clusters in space. A ground-based microwave receiver with respect to Earth would be utilized to block the approaching radiofrequency (RF) energy and convert it once again into useable power. Space-based solar power (SBSP) is the idea of gathering sun-oriented power in space and circulating it to Earth. Potential focal points of gathering sunlight-based vitality in space incorporate a higher accumulation rate and a more drawn out gathering period because of the absence of a diffusing climate, and the likelihood of getting a sun-powered authority in a circling area where there is no night. An extensive portion of approaching sun-based vitality (54–60%) is lost on its way through the Earth's environment by the Impacts of reflection and retention. . Energy-based spacecraft converts daylight into outdoor air microwaves, keeping them away from these disasters and vacations thanks to Earth's pivot, but at an incredible cost due to the cost of generating space. The SBSP is considered a form of conservation or environmentally friendly energy, a sustainable source of energy, and is occasionally considered among the proposals to build the atmosphere. It is appealing to those who want large answers to the rate of natural anthropogenic changes or fatigue of a fuel product, (for example, crest oil).

Different SBSP proposition has been looked into since the mid-1970s, yet none are financially reasonable with present-day space dispatch foundation. The ideate part of this work is as follows. A humble Gigawatt-extend microwave framework, tantamount to a huge business power plant, would require propelling somewhere in the range of 80,000 tons of material to circle, making the expense of vitality from such a framework unfathomably more costly than even present-day sustainable power source. A few technologists hypothesize this may change in the far-off future if an off-world modern base were to be built up that could produce sun-powered power satellites out of space rocks or lunar material, or if radical new space dispatch innovations other than rocketry ought to wind up accessible later on.

In addition to the cost of creating such a framework, the SBSP also identifies a number of mechanical barriers, including the issue of transferring energy from a circle to the surface of the earth for use. Since cables from the surface of the earth to orbiting satellites are not common and are not possible with current construction, SBSP structures for the most part include the use of a certain remote transmission method and its integrated transformations, such as grounding. important channels for receiving objects to gain power on the surface of the earth. The collecting satellite will change beyond the orientation of the sun into positive energy, accelerating the microwave transmitter or laser manufacturer, and transmit this vitality to authority (or microwave rectenna) on Earth's surface. In opposition to appearances of SBSP in prevalent books and computer games, most plans propose

bar vitality densities that are not hurtful if people were to be unintentionally uncovered, for example, if a transmitting satellite's shaft were to the stray course. Yet, the immense size of the accepting radio wires that would be important would even now require enormous squares of land close to the end clients to be acquired and committed to this reason. The administration life of room-based authorities notwithstanding challenges from long haul presentation to the space condition, including debasement from radiation and micrometeoroid harm, could likewise turn into a worry for SBSP.

2. Power Generation and Storage Systems

The define part of this work is explained below. The inverter is commonly arranged in an open region, as close as reasonable to the modules. In a private application, the inverter is routinely mounted to the external sidewall of the home near the electrical basic or sub-sheets. Since inverters make a slight commotion, this should be contemplated while picking the area. The inverter turns the DC power made by the sun oriented fueled sheets into 120-volt AC that can be put to incite use by partner the inverter direct to a submitted electrical switch in the electrical board. The inverter, power age meter, and force net meter are related so power conveyed by sun arranged electric structure will at first be eaten up by the electrical loads at present in the assignment. The degree of impact made by the sun powered based electric structure experiences the electrical board and out onto the electric lattice. To meet the necessities of a gathering framework, a multistage the rectifier was intended to get micropower with rectifiers and doublers with high vitality productivity. A huge number of the voltage doubler can make higher yield voltage, yet will bring about lower productivity. In the power, converter is made out of multistage rectifier which doubler is the essential square of that. The multistage structure was utilized to produce a voltage higher than 1V at the recurrence near 950 MHz. A battery(rechargeable) is a vitality stockpiling gadget is used here, which can also be charged after issuance by providing DC to its terminals. Rechargeable batteries take into account most of the use from the stock, reduce waste and, in large part, give long-term interest rates up to the dollars set for the power of the gadget used. This is true without regard to the high price of rechargeable charging and charging requirement. Frequency is an increasingly common and possible replacement for one-time batteries. The anode of these batteries is used and yet to a lesser extent, taking into account the high cost and discharge.

A. Alternating current coupled storage system

An AC-coupled storage system is associated with the AC matrix mains that administration the property. this sort of course of action is known as a 'two box' arrangement – in light of the fact that there is one 'box' (inverter) for the solar panels and another for the battery bank. The fundamental favorable position of AC-coupled battery stockpiling is that it is the least demanding and by and large more practical approach to retrofit batteries onto a prior sunlight-based PV framework.

B. Direct current coupled storage system

A DC-associated vitality stockpiling framework interfaces with the lattice mains at a similar spot as the solar panels; this normally implies they share a 'half and half' inverter. this is known as a 'one box' arrangement, in light of the fact that there is just a single inverter rather than two. Since they contain fewer segments (which more often than not converts into lower costs), we, for the most part, suggest DC-coupled frameworks for homes considering a fresh out of the plastic new sun oriented and capacity framework (instead of a retrofit). Having a solitary inverter likewise enables family units to get around nearby system limit limitations, which can be restrictively little in certain zones.




Figure 1: Overview of Tx and Rx block

3. Power Conversion Efficiency

The efficiency of power conversion (η) is the ratio between the critical yield of the energy conversion machine and the contribution, in terms of energy efficiency. Contribution, just as a valuable harvest can be production, electrical power, machine work, light (radiation), or efficiency of conversion power (η) is the value between the critical yield of the energy conversion machine and the contribution, in terms of energy. Contribution, as an important harvest may be made, electrical energy, mechanical activity, light (radiation), or heat. In many cases, efficiency or vitality is lost, for example as waste heat or vibration. Craftsmanship is a product of vitality, divided by the inclusion of vitality, and is valued as a standard. A good process will have 100% efficiency. Wout = the function or vitality of a process. In many cases, efficiency or vitality is lost, for example as waste heat or vibration. Craftsmanship is a product of vitality, divided by the inclusion of vitality, and is valued as a standard. A good process will have 100% efficiency. Wout = the work or vitality delivered by a procedure.

The rectifier control transformation efficiency is characterized as the proportion of yield power P_{out} to the info power P_{in} . The information power can be thus spoken to as the aggregate of yield control furthermore, the loss of the rectifier P_{Loss} . PCE is given by

$$PCE = \frac{P_{out}}{P_{in}} = \frac{P_{out}}{P_{out} + P_{Loss}}$$

$$= \frac{P_{out}}{P_{out} + N \cdot P_{diode}}$$

where N denotes number of diode stages and P_{diode} denotes individual diode power loss which is given by

$$P_{diode} = \frac{P_{frwd}}{P_{rev}}$$

4. Rf Signal Based Harvesting System

The vitality collecting from RF signals requires its block attempt of EM waves from nature and after that changed over to DC signal. This idea is normally named as "Rectenna". The prototype model is depicted in Figure 2. However, these frameworks are unfit to convey the steady yield for the dependable task of the different gadgets. In this way, an endeavor has been made and another vitality reaping framework is proposed Embedded control.




Figure 2: Prototype for RF signal energy harvesting system

In the proposed framework, a radio wire goes about as a transducer which can transmit and get the EM waves. It is able to change over RF sign to electrical sign and the other way around. At the recipient side, the receiving wire blocks the EM waves and creates a limited quantity of voltage. In this framework, the different sorts of receiving wires, for example, Dipole, Microstrip, Spiral, Coplanar, Spiral, Yagi-Uda, fix, and allegorical can be used. However, the choice of a receiving wire ends up the basic issue as a little size receiving wire blocks less EM signal through the bigger become unrealistic. To remove the greatest control from a sustainable power source, the vitality reaping circuit is required to coordinate its info impedance to source impedance. Be that as it may, the determination of the best possible receiving wire is pivotal to accomplish the upgraded presentation from the tuner circuit.




Figure 3: Vmax from three different types of antenna

Figure 3 plots the analysis of V_{max} from three different types of antenna after testing and verification. For long separation gathering FM signal (by and large 30 MHz to 3 GHz), the Yagi-Uda is a most loved decision for the last numerous years. It is because of the way that offers the great directional properties and boosts the sign solidarity to the ideal recurrence. The Yagi receiving wire is a limited band receiving wire appropriately utilized for FM channels because of good adequacy also, directivity. In addition, it has the best increase for size and limited radiation essential flap. It comprises of dynamic components (dipole), directors, and reflectors. For the most part, the length of the dipole ranges from the 0.45λ to 0.49λ . Length of the reflector is 5% more noteworthy

than dipole while, executives are 5% littler than dipoles. The addition of a reception apparatus can be increment by including the directors and streamlining the separating among them.¹¹ In this exploration work, seven Aluminum elements based (5 directors, 1 dipole, and 1 reflector) Yagi-Uda receiving wire is utilized. The presentation of the framework is reliant on the great impedance coordinate between the feeder and receiving a wire. It is conceivable to differ the feed impedance of Yagi-Uda reception apparatus by modifying the space between the components^[7]. In any case, it is continuously unrealistic to modify the separation between the components. Along these lines, other procedure, for example, Balun become mainstream as it is a clear and straightforward strategy, incredibly used to coordinate the assortment of impedance proportion. In the proposed methodology, seven components Yagi-Uda reception apparatus is utilized for the different experimentations. The reception apparatus is as of now furnished with Balun game plan for the impedance coordinating which is straightforwardly associated the tuner circuit. The peak (maximum) voltage measured from three antenna of various types has appeared in the following graphical representation as follows.

5. Distinctive Applications

RF force can be utilized to charge or work a wide scope of low-tech gadgets. Close to a sluggish transmitter, this force can be utilized to stream charging different devices including the accompanying GPS or RLTS names, wearable recovery sensors, and buyer equipment, for instance, a computerized manual for singular clients and headsets. Over the long haul, force can be utilized for battery use with or without far off battery sensors for HVAC control and mechanical building, assistant testing, and present day control. Contingent upon the vitality needs and capacity of the system, vitality can be sent constantly, to an assigned territory, or on demand. With incredible affectability to sensors, a significant cost-sparing capacity can be considered by disposing of future batteries. The accessible force from the 3W transmitter will be low milliwatts inside a couple of feet and a few microwatts at around 40 meters. This dynamic level is best utilized for contraptions with low control use and long or ordinary installment cycles. By and large, contraptions that last more, months, or years in a solitary battery setting are bound to be distantly controlled by RF power. For certain applications that expansion battery life or measure the remainder of the microcontroller are adequate approval including RF-based innovation that utilizes vitality and vitality assortment innovation. An exchange framework can be set up in the workplace to give distant force in a room-room building, or in a multi-to-mass charging portfolio. Phones can be utilized as an adaptable force hotspot for different sans battery devices. Think about a wireless that drives a without battery, sensor-detecting gadget that sends information via telephone through a regularly utilized meeting, for instance, Wi-Fi, Bluetooth, or ZigBee. This data can be shown locally in the handset or called to test supervisors. power cast authoritatively exhibited this application utilizing the RF vibrator around the iPhone.

Items with implanted remote force innovation can be shielded from natural conditions, for example, stickiness and client access. In addition, connectors and cables can be disconnected. Product reliability and life cycle can be greatly improved as a result. If you list the appropriate RF source, charging is automatic and obvious to the end user who offers more usage. With Powercast elements, most battery chemicals and charging units can be supported allowing for high flexibility to save power.

6. Conclusion

Capturing sun-based power in space for use as vitality on Earth has been around since the start of the space age. Over the most recent couple of years, in any case, researchers around the world and a few analysts at the Energy Department. On earth, sun-based power is significantly diminished by night, overcast spread, climate, and regularity. Approximately 30 percent of all approaching sun-powered radiation never makes it ground level. In space the sun is continually sparkling, the tilt of the Earth doesn't avert the accumulation of intensity and there's no environment to lessen the force of the sun's beams. This makes putting sun powered boards into space an enticing probability. Moreover, SBSP can be utilized to get dependable and clean vitality to individuals in remote networks far and wide, without depending on the customary framework to a huge nearby power plant.

References

1. Lee, Donggu, et al. "A CMOS Rectifier with 72.3% RF-to-DC Conversion Efficiency Employing Tunable Impedance Matching Network for Ambient RF Energy Harvesting." 2018 International SoC Design Conference (ISOCC), 2018, doi:10.1109/isocc.2018.8649983.
2. E. E. Reber, R. L. Michell, and C. J. Carter, "Oxygen absorption in the Earth's atmosphere," Space solar power station (SSPS) and microwave power transmission (MPT)H. Matsumoto, 2003 IEEE Topical Conference on Wireless Communication Technology Aerospace Corp., Los Angeles, CA, Tech. Rep. TR-0200 (420-46)-3, Nov. 1988.
3. S. K. S. Raja, R. Rishi, E. Sundaresan and V. Srijit, "Demand based crop recommender system for farmers," 2017 IEEE Technological Innovations in ICT for Agriculture and Rural Development (TIAR), Chennai, 2017, pp. 194-199, doi: 10.1109/TIAR.2017.8273714.
4. X. Gu, S. Hemour and K. Wu, "Enabling Far-Field Ambient Energy Harvesting Through Multi-Physical Sources," Asia-Pacific Microwave Conference (APMC), Kyoto, 2018, pp. 204-206, doi: 10.23919/APMC.2018.8617574.

5. Merz, Christian, et al. "Design and Optimization of a Radio Frequency Energy Harvesting System for Energizing Low Power Devices." 2014 International Conference on Applied Electronics, 2014, doi:10.1109/ae.2014.7011703.
6. Kiruthika, U., Somasundaram, T.S. & Raja, S.K.S. Lifecycle Model of a Negotiation Agent: A Survey of Automated Negotiation Techniques. Group DecisNegot (2020). <https://doi.org/10.1007/s10726-020-09704-z>
7. Sampathkumar, A., Murugan, S., Rastogi, R., Mishra, M.K., Malathy, S. and Manikandan, R., 2020. Energy Efficient ACPI and JEHDO Mechanism for IoT Device Energy Management in Healthcare. In Internet of Things in Smart Technologies for Sustainable Urban Development (pp. 131-140). Springer, Cham.